Lexmark MS811n 1200 x 1200 DPI A4

Brand : Lexmark Product code: 40G0220

Product name : MS811n

Laser, A4, 1200 x 1200 dpi, 63 ppm, 800 MHz, 512MB, 2.4" LCD, 2 x USB 2.0, Gigabit Ethernet, 58 dB, 23650 g, White/Black

Lexmark MS811n. Print technology: Laser. Number of print cartridges: 1, Maximum duty cycle: 275000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 63 ppm. Display: LCD. Network ready. Product colour: Black, White







Printing		Performance	
Colour * Print technology *	X Laser	Sound pressure level (printing) Sound power level (standby)	58 dB 32 dB
Duplex printing *	X	Design	
Maximum resolution *	1200 x 1200 DPI	Product colour *	Black, White
Print speed (black, normal quality, A4/US Letter) *	63 ppm	Display	LCD
Time to first page (black, normal)	4.4 s		CAN/CSA, CSA, ICES, BSMI, CNS, VCCI, US FDA, FCC, UL, IEC, EN/IEC,
Features		Certification	CE, CB IEC, EN, GS TUV, SEMKO, UL
Maximum duty cycle *	275000 pages per month 5000 - 30000 pages per month		AR, CS, TUV Rh, SMA C-tick, CCC, CISPIR, EK Mark, N Mark, ECMA, TED
Recommended duty cycle		System requirements	
Printing colours * Number of print cartridges *	Black 1	Windows operating systems	1
	PCL 5Ce, PCL 6, PDF 1.7, PostScript	supported	✓
Page description languages *	3, PPDS, XML	Mac operating systems supported	×
Input & output capacity		Linux operating systems supported	Windows Server 2003, Windows
Total number of input trays * Total input capacity *	2 650 sheets	Server operating systems supported	Server 2003 v64 Windows Server
Total output capacity * Maximum number of input trays	550 sheets 6	Other operating systems supported	✓
Maximum input capacity	4400 sheets	Operational conditions	
Maximum output capacity	2550 sheets	Operating temperature (T-T)	16 - 32 °C
Paper handling		Operating relative humidity (H-H)	8 - 80%
Maximum ISO A-series paper size *	A4	Operating altitude	0 - 2896 m
Maximum print size	216 x 356 mm	Operating temperature (T-T)	60 - 90 °F
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper, Transparencies A4, A5, A6 Executive, Folio, Letter, Oficio, Legal	Sustainability	
ISO A-series sizes (A0A9) *		Sustainability certificates	ENERGY STAR
Non-ISO print media sizes		Weight & dimensions	
JIS B-series sizes (B0B9)	B5	Weight	23.6 kg
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	Dimensions (WxDxH)	425 x 536 x 420 mm
Paper tray media weight (imperial)	7.26 - 21.3 kg (16 - 47 lbs)	Packaging data	
Ports & interfaces		Package weight	27.4 kg
Standard interfaces	USB 2.0		

Ports & interfaces		Other features	
USB 2.0 ports quantity	2	Networking features	Gigabit Ethernet
Network Network ready	1		Windows XP (32/64-bit) Windows Server 2003 (32/64-bit) Windows Vista (32/64-bit) Windows Server 2008 (32/64-bit) Windows 7 (32/64- bit) Windows Server 2008 R2 Novell NetWare 6.5 Open Enterprise Server Novell NetWare 5.1(SP 6+), 6.0(SP 3+) SUSE Linux Enterprise Server 10, 11 SUSE Linux Enterprise Desktop 10, 11 Red Flag Linux Desktop 6.0 Linpus Linux Desktop 9.6 Debian GNU/Linux 5.0, 6.0 Red Hat Enterprise Linux WS 4.0, 5.0, 6.0 Ubuntu 11.04, 11.10, 12.04 openSUSE 11.3, 11.4, 12.1
Wi-Fi *	×	Compatible operating systems	
Ethernet LAN *	1		
Security algorithms	802.1x RADIUS, LEAP, MD5, PEAP, SSL/TLS		
Supported network protocols (IPv4)	TCP/IP, AppleTalk, UDP, TCP		
Supported network protocols (IPv6)	TCP/IP		
Management protocols	HTTP, HTTPs, SNMP v3, WINS, IGMP, BOOTP, RARP, APIPA, DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger		
Performance			PCLinuxOS 2011.9 Mint 9, 10, 11, 12 Fedora 14, 15 Sun Solaris SPARC
Internal memory *	512 MB		9, 10 HP-UX 11.11, 11.23, 11.31
Maximum internal memory	2560 MB		Sun Solaris x86 10, 11 IBM AIX 5.3, 6.1, 7.1
Processor frequency	800 MHz	Power LED	√
		Stand-by LED	✓
		Finishing option	✓
		Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u
		Package dimensions (WxDxH)	615 x 535 x 564 mm





734646347921

0734646347921

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.